


# Composite "Push-In" Tube Fittings


## Fractional Inch size tubing & NPT threads

### Union Tee




Tube O.D. in	Part Number	A in	B in	C in	oz
1/8	P56422	0.33	0.75	0.57	0.15
5/32	P56411	0.33	0.75	0.57	0.14
3/16	P56433	0.43	1.07	0.85	0.58
1/4	P56444	0.43	0.89	0.93	0.22
5/16	P56455	0.53	1.16	0.91	0.32
3/8	P56466	0.63	1.34	1.02	0.64
1/2	P56488	0.87	1.81	1.38	1.74

### Union Reducer Tee




Tube O.D. 1 (in)	Tube O.D. 2 (in)	Part Number	A in	B in	C in	oz
1/4	1/8	P56442	0.43	0.93	0.73	0.35
3/8	1/4	P56464	0.63	1.28	1.00	0.65
1/2	3/8	P56486	0.87	1.81	1.38	0.75

### Straight Union



Tube O.D. in	Part Number	A in	B in	oz
1/8	P56222	0.34	0.97	0.11
5/32	P56211	0.33	0.98	0.07
3/16	P56233	0.43	1.44	0.39
1/4	P56244	0.43	1.16	0.14
5/16	P56255	0.53	1.50	0.25
3/8	P56266	0.63	1.65	0.40
1/2	P56288	0.87	2.17	0.95

### Straight Union Reducer



Tube O.D. 1 (in)	Tube O.D. 2 (in)	Part Number	A in	B in	oz
1/8	1/4	P56242	0.43	1.32	0.34
3/8	1/4	P56264	0.63	1.61	0.50

For applications involving prolonged exposure to ultraviolet (UV) light, we suggest using black tubing for extended life.

